



CATALOG NUMBER	TYPE
PROJECT NAME	DATE

SPECIFICATIONS

FEATURES

- High-capacity thermoplastic EXIT-EM combo with remote capability
- Designed for wall mount only
- Remote capable: choice of 30W or 50W unit capacity at 6V
- Part of Astralite's quick ship program

CONSTRUCTION

- UV-stable, impact-resistant thermoplastic housing; meets UL94V-0 flame rating
- EXIT letters are 6" tall with 3/4" stroke; 100 ft viewing distance

LAMP

- Utilizes two fully-adjustable 1W LED heads in emergency mode
- Face plate is illuminated by long-lasting high-output AlInGaP LEDs with a rated life of 10+ years

ELECTRONICS

- Dual-voltage input capability: 120/277V
- Low-voltage disconnect
- AC lockout installation
- Brownout protection
- AC indicator light with test switch

BATTERY

- Lead-acid battery is standard, and provides a minimum of 90 minutes of illumination in emergency mode
- Nickel-cadmium battery offered as an option
- Operating temperature range: 10-40° C

COMPLIANCE

- Meets or exceeds UL 924, NFPA 101, NEC and OSHA illumination standards

WARRANTY


- 5-year warranty on housing and electronics. Battery is prorated

TP-500-LED

REMOTE CAPABLE THERMOPLASTIC COMBINATION UNIT



DIMENSIONS



ORDERING GUIDE

MODEL	TOTAL UNIT WATTS	LETTER COLOR	HOUSING COLOR	INTEGRAL LAMPS	OPTIONS
TP-500-LED Remote Capable Thermoplastic Combination Unit	30 30 Watts	R Red	W White	2x1 2 x 1W L.E.D.	SD Self Diagnostics 220 220 VAC Input NC Nickel Cadmium Battery
	50 50 Watts	G Green	B Black	2x3 2 x 3W L.E.D.	